

Bedside™ Single-Chamber Temporary Cardiac Pacemaker

Discover the Difference™



Features

- Single-Chamber Pacing - 4 Modes
- Rapid Atrial Pacing – 80-800 ppm
- Constant Voltage Output up to 12 volts
- Pacing and Sensing LED indicators
- Low Battery Indicator– LED and Tone
- Large Faceplate and knobs - User Friendly
- Built-in bedrail hanger
- Redel® Terminal for quick easy connection
- Defibrillation Protected

Bedside™
REF 4170
SUMMARY OF MODES AND PARAMETERS*

Modes/Parameters	Values	Steps/Units
Modes	VVI, VOO AAI, AOO	
Basic Rates (ppm)	30 – 200	Variable
Rapid Stimulation (ppm)	60-800	Variable
Pulse Amplitude (Volts)	0.1-15	Variable
Pulse Width (ms)	1.8	Fixed
Sensitivity (mV)	0.2-16	Variable
Refractory Periods (ms)	250	Fixed
Dimensions (cm)	17.8 x 13.7 x 11.2	
Weight with battery	1,600 grams	
Battery Life	504 hours (2 x 9 V alkaline)	

P A C E M E D I C A L

Pace Medical, Inc.
391 Totten Pond Road
Waltham, MA 02451 USA
Tel: 781-890-5656
Fax: 781-890-4894
www.pacemedicalinc.com

Caution: Federal (USA) law restricts this device to use by or on the order of a physician.

*Nominal specifications. See manual for additional specifications and details.

Bedside™ is a trademark of Pace Medical, Inc.

26 January 2009